



iQ100, wall-mounted cooker hood, 90 cm, Stainless steel LC94PCC50M



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

✓ The 380 m³/h extraction rate supplies clean air when cooking.

Features

Technical Data

Typology : Wall-mounted
Approval certificates : CE, G-Mark, VDE
Length electrical supply cord : 120 cm
Height of the chimney : 410-765/410-765 mm
Height of product, without chimney : 250 mm
Net weight : 13.6 kg
Type of control : mechanical
Number of speed settings : 3
Maximum output air extraction : 380 m³/h
Maximum output recirculating air : 235 m³/h
Number of lights : 2
Noise level : 64 dB(A) re 1 pW
Diameter of air outlet : 150 mm
Grease filter material : Washable aluminium
Odour filter : No
Operating Mode : Convertible
Optional accessories : LA10KPA6
Type of lamps used : LED
Total power of the lamps : 10 W
Grease filter type : Kasette
Connection Rating : 135 W
Voltage : 220-240 V
Frequency : 50 Hz
Plug type : GB plug
Installation typology : Wall-mounted
Material body : Stainless steel
Approval certificates : CE, G-Mark, VDE
Plug type : GB plug
Dimensions of the product, with chimney (if exists) (in) : / x x
Dimensions of the packed product : 15.74 x 39.76 x 22.83
Net weight : 30.000 lbs
Gross weight : 34.000 lbs
Motor location : Integrated motor in hood body
No-return airflow flap : No
Length electrical supply cord : 120 cm
Dimensions of the product, with chimney (if exists) : 790-1015 x 898.0 x 470.0 mm
Dimensions of the packed product (HxWxD) : 400 x 1010 x 580 mm
Net weight : 13.6 kg
Gross weight : 15.3 kg



4 242003 802366



iQ100, wall-mounted cooker hood, 90 cm, Stainless steel LC94PCC50M

Features

Variant:

Design:

- Appliance colour: stainless steel
- Wall mounted hood

Comfort:

- Suitable for ducted or re-circulated extraction
- 3 speeds
- push buttons for extractor speeds and light
- Metal grease filter, dishwasher safe

Environment and safety:

- Energy Efficiency Class: D*
- Average Energy Consumption: 72.8 kWh/year*
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*

Technical information:

- Ducted extraction rate according to DIN/EN 61591 max. 380 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW (50 dB(A) re 20 µPa sound pressure)
- Noise min./max. Normal Level: 53/64 dB*
- Light Intensity: 1000 lux
- Colour Temperature: 4000 K
- Power rating: 135 W

Measures:

- Dimensions exhaust air (HxWxD): 790 - 1015 x 898 x 470 mm
- Dimensions recirculating (HxWxD): 790 - 1015 x 898 x 470 mm
- 150 mm diameter pipe

* In accordance with the EU-Regulation No 65/2014



iQ100, wall-mounted cooker hood, 90 cm, Stainless steel LC94PCC50M

Dimensioned drawings

