



iQ300, wall-mounted cooker hood, 90 cm, Stainless steel LC97BHM50B



Extractor hood in Box design with high extraction rate.

- ✓ Thanks to touchControl the power level and the LED light can be selected directly.
- ✓ Intensive setting with automatic after revert setting
- ✓ Optimal visibility and atmosphere when cooking - LED light.

Features

Technical Data

Typology : Wall-mounted
Length electrical supply cord : 130 cm
Height of the chimney : 583-912/583-1022 mm
Height of product, without chimney : 53 mm
Net weight : 13.6 kg
Type of control : Electronic
Maximum output air extraction : 454 m³/h
Boost position output recirculating : 499 m³/h
Maximum output recirculating air : 404 m³/h
Boost position air extraction : 739 m³/h
Number of lights : 2
Noise level : 65 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable stainless steel
Odour filter : No
Operating Mode : Convertible
Optional accessories : LZ00XXP00, LZ10DXA00, LZ10DXU00, LZ10FXJ00, LZ11DXB14, LZ11DXI14, LZ11DXI16, LZ11FXC56, LZ31XXB16, LZ11FXD51, LZ12250, LZ12350, LZ50960, LZ50961
Type of lamps used : LED
Grease filter type : Kasette
Connection Rating : 255 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Plug type : GB plug
Installation typology : Wall-mounted
Material body : Stainless steel
Plug type : GB plug
Dimensions of the product, with chimney (if exists) (in) : / x x
Dimensions of the packed product : 19.29 x 25.59 x 40.55
Net weight : 30.000 lbs
Gross weight : 42.000 lbs
Motor location : Integrated motor in hood chimney
No-return airflow flap : No
Length electrical supply cord : 130 cm
Dimensions of the product, with chimney (if exists) : 635-1075 MM x 900.0 x 500.0 mm
Dimensions of the packed product (HxWxD) : 490 x 650 x 1030 mm
Net weight : 13.6 kg
Gross weight : 19.0 kg





iQ300, wall-mounted cooker hood, 90 cm, Stainless steel LC97BHM50B

Features

Variant:

Design:

- 90 cm Chimney hood
- Wall mounted hood
- Appliance colour: stainless steel

Comfort:

- Suitable for ducted or recirculated operation
- For recirculated extraction or CleanAir recirculation kit (accessory) needed
- touchControl with Electronic display
- 3 speed + intensive operation
- Twin channel high performance fan motor
- Metal grease filter, dishwasher safe
- Capacitor energy efficient

Technical information:

- Extraction rate according to DIN/EN 61591 ø 15 cm: max. Normal 453 m³/h Intensive 739 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
 - Max. normal use: 65 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
 - Intensive: 65 dB(A) re 1 pW (61 dB(A) re 20 µPa sound pressure)
- Noise min./max. Normal Level: 52/65 dB*
- Power rating: 255 W

Measures:

- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
 - 703 x 900 x 500mm - mounting with outer chimney
 - 833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Electrical cable length 1.3 m
- 2 x 1,5W LED
- Light Intensity: 214 lux
- Colour Temperature: 3500 K

Environment and safety:

- Energy Efficiency Class: B*
- Average Energy Consumption: 62.5 kWh/year*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

* In accordance with the EU-Regulation No 65/2014



iQ300, wall-mounted cooker hood, 90 cm, Stainless steel LC97BHM50B

Dimensioned drawings

